



US005602572A

# United States Patent [19]

## Rylander

[11] **Patent Number:** **5,602,572**  
 [45] **Date of Patent:** **Feb. 11, 1997**

[54] **THINNED HALFTONE DOT PATTERNS FOR INKJET PRINTING**

[75] Inventor: **Richard L. Rylander**, Stillwater, Minn.

[73] Assignee: **Minnesota Mining and Manufacturing Company**, St. Paul, Minn.

[21] Appl. No.: **295,603**

[22] Filed: **Aug. 25, 1994**

[51] Int. Cl.<sup>6</sup> ..... **B41J 2/205**

[52] U.S. Cl. .... **347/15; 347/131; 347/183; 347/240; 358/298**

[58] Field of Search ..... **347/15, 43, 107, 347/131, 183, 251, 254, 240; 358/298, 534, 456; 382/257, 260, 302, 308**

### [56] References Cited

#### U.S. PATENT DOCUMENTS

4,084,259 4/1978 Cahill et al. .... 364/900  
 4,651,175 3/1987 Tazaki ..... 347/9  
 5,353,387 10/1994 Petschik et al. .... 395/109  
 5,416,612 5/1992 Ingraham et al. .... 358/501

#### FOREIGN PATENT DOCUMENTS

0513989A2 11/1992 European Pat. Off. .... B41J 2/205  
 0516420A2 12/1992 European Pat. Off. .... B41J 2/205

WO91/14578 10/1991 WIPO ..... B41J 2/505

*Primary Examiner*—Benjamin R. Fuller

*Assistant Examiner*—Craig A. Hallacher

*Attorney, Agent, or Firm*—Carolyn A. Bates; Steven J. Shumaker

### [57] ABSTRACT

A set of thinned halftone dot patterns useful in inkjet printing comprises a plurality of halftone cells corresponding to respective shade values. Each of the halftone cells includes a plurality of addressable points, with at least some of the points being turned "on" to define a halftone dot pattern, and at least some of the "on" points defining a core component of the halftone dot pattern being selectively turned "off", thereby producing a thinned halftone dot pattern. The thinned halftone dot patterns enable the use of higher addressability in an inkjet printing system to achieve a wider range of shade values while avoiding undesirable over-inking of printed halftone dot patterns due to excessive overlap between printed ink spots. The thinned halftone dot patterns prevent significant overlap between adjacent ink spots in the core, or "interior", component when the halftone dot pattern is printed by the inkjet printing system, but preserves the entire edge component to maintain desired halftone cell definition. Thinned halftone cells can be stored in a memory as "glyphs" and retrieved by an inkjet printing system to print higher addressability halftone images with enhanced quality and a wider range of shade values.

**26 Claims, 7 Drawing Sheets**

